
GODKENDELSESINDEHAVER:

RatéL ApS
Centervej 2
DK-6000 Kolding
Phone: +45 69 89 86 86
Web: www.ratel.dk

Rat blocker for horizontal sewage pipes

RATÉL


models ET – 10 and ET – 20

dim. ø110, ø160, ø200 and ø250

MAKE:

RatéL ApS, Denmark

MARKING:

- Type
- Approval number
- Approval mark: 

QUALITY CONTROL:

The holder of this approval maintains a compulsory control agreement with the Danish Technological Institute, Aarhus, Denmark.

CONDITIONS FOR INSTALLATION AND USE:

The rat blocker is installed in horizontal sewage pipes in connection with transitions to cleaning- and inspection chambers and manholes.

The rat blocker can be used in various types of pipes, and installation of the rat blocker must be carried out in accordance with the instructions provided by the holder of this approval.

DESCRIPTION AND TECHNICAL DATA:

The rat blocker is made of acid-proof stainless steel.

The rat blocker consists of a U-shaped profile with suspended flaps. The flaps, located at the end of the direction of water flow, are fitted with a locking device which can lock the flaps, rendering the pipe impassable to rats.

When a rat encounters the blocker in trap model ET 10, the vermin is directed to a chamber where it is killed by high voltage. Trap model ET 20 also directs the rat into a chamber, however killing the vermin by a piston hitting it with great force. The rats are subsequently led away by the waste water stream.

The device can be installed, operated and demounted without the fitter entering the sewer.